



# POLYCARBONATE FILM

**Polycarbonate Film** has a very small thickness and possesses an extraordinary variety of properties and advantages. It distinguishes itself because it is transparent, resistant both to high and low temperatures, stable in its dimensions, UL self-extinguishing, chemically resistant, abrasion resistant. Polycarbonate Film is particularly suitable for the following purposes: silk-screen, offset and flexographic printing, decoration through hot impression or vacuum metalization without pre-treatments, die-cutting with small tolerance; embossing with the best definition of all details.

**Applications:** Polycarbonate Film can be used to product plates, instrument panels for vehicles, conductive graphics for membrane switches, back lighted instrument panels, visualizers.

RANGE AT STOCK			
Article code	Article description	Thickness (mm)	Size (mm)
003ILL01250930	TRANSPARENT GLOSSY/GLOSSY POLYCARBONATE FILM	0,125	930 x 396 m
003ILL01750930		0,178	930 x 335 m
003ILL02500930		0,250	930 x 244 m
003IFLL0500		0,500	2000 x 1000
003PEL0750		0,750	2050 x 1250
003SLP010		1,000	2050 x 1250
003ILM02500915	TRANSPARENT GLOSSY/MATT POLYCARBONATE FILM with protective film	0,250	930 x 320 m
003IMM01780930	TRANSPARENT MATT/MATT POLYCARBONATE FILM	0,178	930 x 457 m
003IMM02500930		0,250	930 x 320 m
003IMM03800930		0,380	930 x 213 m
003IMM05000930		0,500	930 x 168 m